

HiBATT

High Bond Acrylic Transfer Tape

Part No. 9620-T

2-Sided Sealing and Bonding Scrim Tape

DESCRIPTION

9620-T is an aggressive brown, PETP, scrim coated on both sides with a water borne modified Acrylic Adhesive. ***Spray Glue on a roll!*** Tape is supplied on a natural siliconized paper release liner. The adhesive system of this double coated tape has excellent tack, combined with a high adhesive strength, and will bond well to nearly all materials; even to difficult surfaces like foams, PE and PP films. It has excellent temperature, UV, aging, and water vapor resistance. **Special adhesive formulation provides very good anti-migration of plasticizers.**

FEATURES

- Durability with flexibility
- Rough surface bonding
- Expands and contracts with substrate
- Water vapor resistant
- Acrylic adhesive provides long-term performance

SUGGESTED APPLICATIONS

- Bonds and seals plastic sheeting
- Affix wall signage
- Permanent bonding of various materials such as fabrics, wallboard, plastics—including PVC, metal and wood surfaces
- Laminate to foams and films—scrim reinforcement provides improved laydown

ADVANTAGES

- Bonds and seals materials in a single step
- No VOC's or sticky overspray like common spray adhesives
- Will not crack, become brittle or shrink
- Protective cover stays in place protecting second bond surface
- May be built up in layers for extra bond strength when needed

AVAILABLE PACKAGING

4" x 108' (approx.) roll, 12 rolls per case

TYPICAL PROPERTIES

Backing: PETP Scrim

Adhesive Type: Modified Acrylic

Total Thickness: 9.2 mils

Adhesion: >120 oz / inch

Temp Resistance: to 248°F

UV Resistance: Very Good

Aging Resistance: Very Good

Condensation Resistance: Good to Very Good

Note: All test procedures were conducted by Rhino Hide

INSTRUCTIONS FOR USE

HiBatt must be applied to substrates that are clean, dry and free of dust and grease. Do not apply the tape <40° and >110°F. Any traces of grease, paint, loose material must be systematically removed.

After placing tape into position, apply pressure to protective backing with a rubbing motion. Do not remove protective backing until ready to adhere material to second side.

A single band of HiBATT is sufficient for most applications. Double rows are recommended in areas of excessive moisture.

WARNING: Do not stick HiBatt to anything you don't want it to stay stuck to!

LIMITED REMEDY

Follow the instructions carefully. If your application is not covered by these instructions, call 863-665-0203 before using this product. Buyer agrees that if HomeWood Solutions' products are proved defective, the user's exclusive remedy will be, at HomeWood Solutions election, to replace the defective product or refund the purchase price for the defective quantity.